

Extruded slats & Table of diameter

(Table of diameter are approximate!)

Quality slats from the huge products of extruded aluminum profiles, long lasting for many years, having broad side thickness, and range of colors from every color of RAL (the guide rails are also compatible for foamed slats).

| | <p>Extruded mini 33 mm slat General information: Thickness of slat.....8 mm Side thickness.....1 mm Max recommended light opening.....3 x 2.5 m Weight per meter.....7 kg Number of slats per meter (height).....30</p> | <p>Catalog № 110200 guide rail 22 x 28 mm for mini slat</p> | <p>Table of diameter rolling shutter extruded slat 33 mm </p> <table border="1"> <thead> <tr> <th>Opening height (cm)</th> <th>Type of tube</th> <th>Tube 40 mm</th> <th>Tube 60 mm</th> </tr> </thead> <tbody> <tr><td>100</td><td></td><td>112</td><td>123</td></tr> <tr><td>120</td><td></td><td>121</td><td>133</td></tr> <tr><td>140</td><td></td><td>131</td><td>139</td></tr> <tr><td>160</td><td></td><td>140</td><td>146</td></tr> <tr><td>180</td><td></td><td>150</td><td>154</td></tr> <tr><td>200</td><td></td><td>158</td><td>162</td></tr> <tr><td>220</td><td></td><td>166</td><td>169</td></tr> <tr><td>240</td><td></td><td>174</td><td>177</td></tr> <tr><td>260</td><td></td><td>182</td><td>185</td></tr> <tr><td>280</td><td></td><td>190</td><td>192</td></tr> <tr><td>300</td><td></td><td>197</td><td>198</td></tr> </tbody> </table> | Opening height (cm) | Type of tube | Tube 40 mm | Tube 60 mm | 100 | | 112 | 123 | 120 | | 121 | 133 | 140 | | 131 | 139 | 160 | | 140 | 146 | 180 | | 150 | 154 | 200 | | 158 | 162 | 220 | | 166 | 169 | 240 | | 174 | 177 | 260 | | 182 | 185 | 280 | | 190 | 192 | 300 | | 197 | 198 | | | | | | | | | | | | |
|---------------------|--|---|---|---------------------|--------------|-------------|-------------|-------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|--|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|--|-----|-----|-----|-----|-----|-----|-----|-----|-----|--|-----|-----|-----|-----|--|-----|-----|-----|
| Opening height (cm) | Type of tube | Tube 40 mm | Tube 60 mm | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 100 | | 112 | 123 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 120 | | 121 | 133 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 140 | | 131 | 139 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 160 | | 140 | 146 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 180 | | 150 | 154 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 200 | | 158 | 162 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 220 | | 166 | 169 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 240 | | 174 | 177 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 260 | | 182 | 185 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 280 | | 190 | 192 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 300 | | 197 | 198 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | <p>Extruded midi 45 mm slat General information: Thickness of slat.....9 mm Side thickness.....1 mm Max recommended light opening.....3.5 x 2.5 m Weight per meter.....7 kg Number of slats per meter (height).....22</p> | <p>Catalog № 110241 distant guide rail 22 x 65 mm for midi slat</p> | <p>Table of diameter rolling shutter extruded slat 45 mm </p> <table border="1"> <thead> <tr> <th>Opening height (cm)</th> <th>Type of tube</th> <th>Tube 40 mm</th> <th>Tube 60 mm</th> <th>Tube 70 mm</th> </tr> </thead> <tbody> <tr><td>100</td><td></td><td>115</td><td>124</td><td>130</td></tr> <tr><td>120</td><td></td><td>124</td><td>132</td><td>140</td></tr> <tr><td>140</td><td></td><td>135</td><td>149</td><td>155</td></tr> <tr><td>160</td><td></td><td>144</td><td>155</td><td>165</td></tr> <tr><td>180</td><td></td><td>153</td><td>160</td><td>170</td></tr> <tr><td>200</td><td></td><td>162</td><td>168</td><td>175</td></tr> <tr><td>220</td><td></td><td>170</td><td>175</td><td>185</td></tr> <tr><td>240</td><td></td><td>178</td><td>180</td><td>195</td></tr> <tr><td>260</td><td></td><td>184</td><td>186</td><td>200</td></tr> <tr><td>280</td><td></td><td>192</td><td>193</td><td>208</td></tr> <tr><td>300</td><td></td><td>199</td><td>200</td><td>215</td></tr> </tbody> </table> | Opening height (cm) | Type of tube | Tube 40 mm | Tube 60 mm | Tube 70 mm | 100 | | 115 | 124 | 130 | 120 | | 124 | 132 | 140 | 140 | | 135 | 149 | 155 | 160 | | 144 | 155 | 165 | 180 | | 153 | 160 | 170 | 200 | | 162 | 168 | 175 | 220 | | 170 | 175 | 185 | 240 | | 178 | 180 | 195 | 260 | | 184 | 186 | 200 | 280 | | 192 | 193 | 208 | 300 | | 199 | 200 | 215 |
| Opening height (cm) | Type of tube | Tube 40 mm | Tube 60 mm | Tube 70 mm | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 100 | | 115 | 124 | 130 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 120 | | 124 | 132 | 140 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 140 | | 135 | 149 | 155 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 160 | | 144 | 155 | 165 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 180 | | 153 | 160 | 170 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 200 | | 162 | 168 | 175 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 220 | | 170 | 175 | 185 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 240 | | 178 | 180 | 195 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 260 | | 184 | 186 | 200 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 280 | | 192 | 193 | 208 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 300 | | 199 | 200 | 215 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | <p>Extruded 55 mm slat with screw General information: Thickness of slat.....13.4 mm Side thickness.....1 mm Max recommended light opening.....5 x 3 m Weight per meter.....8 kg Number of slats per meter (height).....18</p> | <p>Catalog № 110261 distant guide rail 28 x 90 mm for extruded 55 mm slat</p> | <p>Table of diameter rolling shutter extruded slat 55 mm </p> <table border="1"> <thead> <tr> <th>Opening height (cm)</th> <th>Type of tube</th> <th>Tube 60 mm</th> <th>Tube 70 mm</th> <th>Tube 89 mm</th> </tr> </thead> <tbody> <tr><td>100</td><td></td><td>130</td><td>135</td><td>144</td></tr> <tr><td>120</td><td></td><td>145</td><td>150</td><td>155</td></tr> <tr><td>140</td><td></td><td>155</td><td>160</td><td>168</td></tr> <tr><td>160</td><td></td><td>175</td><td>170</td><td>175</td></tr> <tr><td>180</td><td></td><td>180</td><td>183</td><td>188</td></tr> <tr><td>200</td><td></td><td>187</td><td>190</td><td>195</td></tr> <tr><td>220</td><td></td><td>197</td><td>200</td><td>205</td></tr> <tr><td>240</td><td></td><td>203</td><td>206</td><td>209</td></tr> <tr><td>260</td><td></td><td>206</td><td>213</td><td>215</td></tr> <tr><td>280</td><td></td><td>215</td><td>217</td><td>220</td></tr> <tr><td>300</td><td></td><td>223</td><td>223</td><td>225</td></tr> </tbody> </table> | Opening height (cm) | Type of tube | Tube 60 mm | Tube 70 mm | Tube 89 mm | 100 | | 130 | 135 | 144 | 120 | | 145 | 150 | 155 | 140 | | 155 | 160 | 168 | 160 | | 175 | 170 | 175 | 180 | | 180 | 183 | 188 | 200 | | 187 | 190 | 195 | 220 | | 197 | 200 | 205 | 240 | | 203 | 206 | 209 | 260 | | 206 | 213 | 215 | 280 | | 215 | 217 | 220 | 300 | | 223 | 223 | 225 |
| Opening height (cm) | Type of tube | Tube 60 mm | Tube 70 mm | Tube 89 mm | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 100 | | 130 | 135 | 144 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 120 | | 145 | 150 | 155 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 140 | | 155 | 160 | 168 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 160 | | 175 | 170 | 175 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 180 | | 180 | 183 | 188 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 200 | | 187 | 190 | 195 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 220 | | 197 | 200 | 205 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 240 | | 203 | 206 | 209 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 260 | | 206 | 213 | 215 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 280 | | 215 | 217 | 220 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 300 | | 223 | 223 | 225 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | <p>Extruded 61 mm slat General information: Thickness of slat.....8 mm Side thickness.....1 mm Max recommended light opening.....5.5 x 3 m Weight per meter.....8.5 kg Number of slats per meter (height).....16</p> | <p>Catalog № 110250 distant guide rail 28 x 75 mm for extruded 61 mm slat</p> | <p>Table of diameter rolling shutter extruded slat 61 mm </p> <table border="1"> <thead> <tr> <th>Opening height (cm)</th> <th>Type of tube</th> <th>Tube 70 mm</th> <th>Tube 89 mm</th> <th>Tube 105 mm</th> </tr> </thead> <tbody> <tr><td>100</td><td></td><td>141</td><td>150</td><td>170</td></tr> <tr><td>120</td><td></td><td>155</td><td>160</td><td>180</td></tr> <tr><td>140</td><td></td><td>160</td><td>175</td><td>195</td></tr> <tr><td>160</td><td></td><td>177</td><td>180</td><td>200</td></tr> <tr><td>180</td><td></td><td>191</td><td>194</td><td>214</td></tr> <tr><td>200</td><td></td><td>195</td><td>197</td><td>217</td></tr> <tr><td>220</td><td></td><td>200</td><td>205</td><td>225</td></tr> <tr><td>240</td><td></td><td>206</td><td>209</td><td>229</td></tr> <tr><td>260</td><td></td><td>213</td><td>216</td><td>235</td></tr> <tr><td>280</td><td></td><td>218</td><td>220</td><td>241</td></tr> <tr><td>300</td><td></td><td>223</td><td>225</td><td>245</td></tr> </tbody> </table> | Opening height (cm) | Type of tube | Tube 70 mm | Tube 89 mm | Tube 105 mm | 100 | | 141 | 150 | 170 | 120 | | 155 | 160 | 180 | 140 | | 160 | 175 | 195 | 160 | | 177 | 180 | 200 | 180 | | 191 | 194 | 214 | 200 | | 195 | 197 | 217 | 220 | | 200 | 205 | 225 | 240 | | 206 | 209 | 229 | 260 | | 213 | 216 | 235 | 280 | | 218 | 220 | 241 | 300 | | 223 | 225 | 245 |
| Opening height (cm) | Type of tube | Tube 70 mm | Tube 89 mm | Tube 105 mm | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 100 | | 141 | 150 | 170 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 120 | | 155 | 160 | 180 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 140 | | 160 | 175 | 195 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 160 | | 177 | 180 | 200 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 180 | | 191 | 194 | 214 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 200 | | 195 | 197 | 217 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 220 | | 200 | 205 | 225 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 240 | | 206 | 209 | 229 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 260 | | 213 | 216 | 235 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 280 | | 218 | 220 | 241 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 300 | | 223 | 225 | 245 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | <p>Extruded 100 mm slat General information: Thickness of slat.....28.5 mm Side thickness.....1.8 mm Max recommended light opening.....7 x 7 m Weight per meter.....15 kg Number of slats per meter (height).....10</p> | <p>Catalog № 110280 guide rail 51 x 80 mm for extruded 100 mm slat</p> | <p>Table of diameter rolling shutter extruded slat 100 mm </p> <table border="1"> <thead> <tr> <th>Opening height (cm)</th> <th>Type of tube</th> <th>Tube 130 mm</th> <th>Tube 150 mm</th> </tr> </thead> <tbody> <tr><td>200</td><td></td><td>300</td><td>200</td></tr> <tr><td>250</td><td></td><td>340</td><td>250</td></tr> <tr><td>300</td><td></td><td>360</td><td>300</td></tr> <tr><td>350</td><td></td><td>390</td><td>350</td></tr> <tr><td>400</td><td></td><td>410</td><td>400</td></tr> <tr><td>450</td><td></td><td>420</td><td>450</td></tr> <tr><td>500</td><td></td><td>430</td><td>500</td></tr> <tr><td>550</td><td></td><td>460</td><td>550</td></tr> <tr><td>600</td><td></td><td>480</td><td>600</td></tr> <tr><td>650</td><td></td><td>500</td><td>650</td></tr> </tbody> </table> | Opening height (cm) | Type of tube | Tube 130 mm | Tube 150 mm | 200 | | 300 | 200 | 250 | | 340 | 250 | 300 | | 360 | 300 | 350 | | 390 | 350 | 400 | | 410 | 400 | 450 | | 420 | 450 | 500 | | 430 | 500 | 550 | | 460 | 550 | 600 | | 480 | 600 | 650 | | 500 | 650 | | | | | | | | | | | | | | | | |
| Opening height (cm) | Type of tube | Tube 130 mm | Tube 150 mm | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 200 | | 300 | 200 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 250 | | 340 | 250 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 300 | | 360 | 300 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 350 | | 390 | 350 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 400 | | 410 | 400 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 450 | | 420 | 450 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 500 | | 430 | 500 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 550 | | 460 | 550 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 600 | | 480 | 600 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 650 | | 500 | 650 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | <p>Extruded 45mm slat tilting rolling shutter General information: Thickness of slat.....12.7 mm Side thickness.....0.9 mm Max recommended light opening 1.1 m Weight per meter.....6.8 kg Number of slats per meter (height).....20</p> | <p>Catalog № 11469 Nylon end cups for tilting slat 45mm Kol-Chen model</p> | <p>Catalog № 32002 Hand lever for opening</p> <p>Catalog № 7922E Perforated segment</p> <p>Catalog № 7834E Perforated profile tilting rolling shutter</p> | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |